



**The integrative camera of auto-identify.**  
**Built in auto thermostatic control system with patent.**  
**Continuous 360°rotation ,max 300°/s can be asjusted.**  
**128 preset position.(title can be setup)**  
**3 patterns scan routes.(pattern scan)**  
**Integrated multi-protocol can set ID remotely.**  
**The camera's rotation angle and temperature can be displayed on screen.**  
**channel alarm input,2 channel alarm output.**  
**The dynamic ID can be revised on menu.**

## Technical Specifications

Model	XC-923	XC-927	XC-930
Image Sensor	3.6mm (H) x 2.7mm(V) 1/4CCD		
Video Output	1.0Vp-p 75 Ohm, BNC		
Horizontal Resolution	540TVL(Color) / 570TVL (B/W)		
S/N Ratio	≥50dB		
Min Illumination	0.7Lux (color) 0.1Lux (B/W)	0.4Lux (color) 0.001Lux (B/W)	0.4Lux (color) 0.001Lux (B/W)
Iris Range	F1.6-34,Close	F1.6-34,Close	F1.6-32,Close
Opposite Focus	Auto/Manual		
Focus	23x f=3.84mm-88.4mm (F 1.6 to 3.2)	27x f=3.84mm-103.68mm (F 1.6 to 3.2)	30x f=3.3mm-99mm (F 1.6 to 3.2)
Digital Zoom	23×10		30×8
BLC	On/Off		
White Balance	No		
Electronic Shutter	Auto / Manual		
Control Method	RS485		
Menu Display	ON/OFF (Preset add. Area name, 8 Characters, 3D coordination, Temperature Display)		
Preset Points	128 Presets		
Preset Point Setting Content	Pan (Up, Down, Left and Right), Camera (Multiple/Focus)		
Patrol Tracks	3 Lines		
Privacy Zone	Yes		
Self Study Function	Yes		
Angle Display Function	Yes		
Home Place	Yes		
Alarm Function	4 input/ 2 output		
Left & Right Rotation Range	Continuous 360° Rotation		
Left & Right Speed	0.1° - 300° /s		
Up & Down Rotation Range	0° ~ 90°		
Up & Down Speed	0.1°-120°		
Auto Flip	90° Vertical		
Video Protection	Yes		
Communication Protection	Yes		
Power Protection	Yes		
Metal Protection	IP66		
Power Input	AC24V or DC15V (wide voltage design)		
Operation Temperature	-45°C ~ +50°C		

© Xenyum security products | Data subject to change without notice