



- Key Features**
- 1/3" SONY CCD
 - DSP technology Effio with WDR
 - 72 PCS Small LED
 - IR LED over 60 meters
 - 2.8-12mm Varifocal Lens
 - Defog / Sense-up / Smart-IR

Model	XC-7066	XC-7067
Image Resolution	650TV Lines	720TV Lines
Effective Pixels	752(H)×582(V)	976(H)×582(V)
TV System	PAL/NTSC	
Electronic Shutter	Auto: PAL 1/50-1/100, 000Sec ; NTSC 1/60-1/100, 000Sec	
Sync System	Internal	
Usable Illumination	0.01Lux/F2.0	0.001Lux/F2.0
S/N Ratio	≥50dB	≥52dB
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec	
Focus Length	2.8-12mm	
Focus Control	Manual	
Lens Type	Manual	
Infrared LED	∅ 5X72PCS	
Infrared Distance	60M	
IR Status	Under 10 Lux By CDS	
IR Power On	CDS Auto Control	
Day/Night	Color/ B&W	
White Balance	AUTO	
Gain Control	AUTO	
Noise Reduction	2D NR	3D NR
Weatherproof Housing	YES, IP66	
Anti-cut Bracket	YES, 3-Axis	
IR Cut Filter	NO	YES
Operation Temperature	-10°C ~ +50°C RH95% Max	
Storage Temperature	-20°C ~ +60°C RH95% Max	
Power Source	DC12V±10%, 500mA	
Dimension	312(W) x133(H) x102(D)mm	
Weight	1.8Kg	